

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 01/03/2019

SECTION 1: Identification	
1.1. Identification	
Product form	: Mixture
Product name	: Clean Tap
Product code	: 8115
1.2. Recommended use and restriction	ns on use
Use of the substance/mixture	: Alkaline cleaning compound
1.3. Supplier	
Ace Chemical Products, Inc. 8415 N. 87th Street Milwaukee, WI 53224 - USA T (414) 357-8515 - F (414) 357-8528 info@acechem.com - www.acechem.com	
1.4. Emergency telephone number	
Emergency number	: For help in chemical emergencies, call Chemtrec day or night Chemtrec 1-800-424-9300
SECTION 2: Hazard(s) identificatio	n
2.1. Classification of the substance or	mixture
GHS US classification	
Acute toxicity (oral) Category 4 H302	Harmful if swallowed
	Causes severe skin burns and eye damage
Full text of H statements : see section 16	
2.2. GHS Label elements, including pro	essutionery statements
2.2. GHS Label elements, including pro GHS US labeling	ecautionally statements
Hazard pictograms (GHS-US)	
Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	: H314 - Causes severe skin burns and eye damage H290 - May be corrosive to metals
Precautionary statements (GHS-US)	 P260 - Do not breathe dust/fume/gas/mist/vapors/spray P264 - Wash thoroughly after handling P280 - Wear protective gloves/protective clothing/eye protection/face protection P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P310 - Immediately call a doctor, a POISON CENTER P321 - Specific treatment (see on this label) P363 - Wash contaminated clothing before reuse P406 - Store locked up P406 - Store in corrosive resistant/ container with a resistant inner liner P501 - Dispose of contents/container to
2.3. Other hazards which do not result	t in classification

Unknown acute toxicity (GHS US) 2.4.

Not applicable

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. MIXTURES			
Name	Product identifier	%	GHS US classification
potassium hydroxide, 45%= <conc<50%, aqueous="" solutions<="" td=""><td>(CAS-No.) 1310-58-3</td><td>5 - 15</td><td>Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314</td></conc<50%,>	(CAS-No.) 1310-58-3	5 - 15	Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures general	: Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.
First-aid measures after skin contact	: Wash immediately with lots of water (15 minutes)/shower. Do not apply (chemical) neutralizing agents. Remove clothing while washing. Do not remove clothing if it sticks to the skin. Cover wounds with sterile bandage. Consult a doctor/medical service. If burned surface > 10%: take victim to hospital.
First-aid measures after eye contact	: Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Cover eyes aseptically. Take victim to an ophthalmologist. Do not apply neutralizing agents. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	: Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Do not give activated charcoal. Do not give chemical antidote. Immediately call a poison center or doctor/physician. Take the container/vomit to the doctor/hospital. Ingestion of large quantities: immediately to hospital.
4.2. Most important symptoms and effect	s (acute and delayed)
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries	: Causes severe skin burns and eye damage.
Symptoms/injuries after inhalation	: EXPOSURE TO HIGH CONCENTRATIONS: Dry/sore throat. Coughing. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. FOLLOWING SYMPTOMS MAY APPEAR LATER: Possible laryngeal spasm/oedema. Risk of lung oedema. Respiratory difficulties.
Symptoms/injuries after skin contact	: Caustic burns/corrosion of the skin. Slow-healing wounds.
Symptoms/injuries after eye contact	: Corrosion of the eye tissue. Permanent eye damage.
Symptoms/injuries after ingestion	: Vomiting. Diarrhoea. Burns to the gastric/intestinal mucosa. Possible esophageal perforation. Bleeding of the gastrointestinal tract. Shock. AFTER ABSORPTION OF HIGH QUANTITIES: Disturbances of consciousness.
Chronic symptoms	: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Dry skin. Skin rash/inflammation. Possible inflammation of the respiratory tract.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures			
5.1. Suitable (and unsuitable) extinguishin	ig media		
Suitable extinguishing media	EXTINGUISHING MEDIA FOR SURROUNDING FIRES: Adapt extinguishing media to the environment. Foam. Dry powder. Carbon dioxide. Water spray. Sand.		
Unsuitable extinguishing media	Do not use a heavy water stream.		
5.2. Specific hazards arising from the chemical			
Fire hazard	DIRECT FIRE HAZARD. Non combustible. INDIRECT FIRE HAZARD. Reactions involving a fire hazard: see "Reactivity Hazard".		
Explosion hazard	INDIRECT EXPLOSION HAZARD. Reactions with explosion hazards: see "Reactivity Hazard".		
Fire hazard	DIRECT FIRE HAZARD. Non combustible. INDIRECT FIRE HAZARD. Reactions involving a fire hazard: see "Reactivity Hazard".		

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Special protective equipment an	nd precautions for fire-fighters	
Firefighting instructions	Cool tanks/drums with water spray/remove them into safety. Dilute toxic gases with water spray. Take account of toxic fire-fighting water. Use water moderately and if possible collect or contain it. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.	
Protection during firefighting	: Heat/fire exposure: compressed air/oxygen apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.	
SECTION 6: Accidental release m	leasures	
6.1. Personal precautions, protective equipment and emergency procedures		
General measures	: Isolate from fire, if possible, without unnecessary risk.	
6.1.1. For non-emergency personnel		
Protective equipment	: Gloves. Face-shield. Corrosion-proof suit. Large spills/in enclosed spaces: compressed air apparatus. Large spills/in enclosed spaces: gas-tight suit. See "Material-Handling" to select protective clothing.	
Emergency procedures	: Mark the danger area. No naked flames. Wash contaminated clothes. Large spills/in confined spaces: consider evacuation. In case of hazardous reactions: keep upwind. In case of reactivity hazard: consider evacuation. Evacuate unnecessary personnel.	
6.1.2. For emergency responders		
Protective equipment	: Equip cleanup crew with proper protection.	
Emergency procedures	: Ventilate area.	
6.2. Environmental precautions		

Prevent soil and water pollution. Prevent spreading in sewers. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containme	6.3. Methods and material for containment and cleaning up	
For containment	: Contain released substance, pump into suitable containers. Consult "Material-handling" to select material of containers. Plug the leak, cut off the supply. Dam up the liquid spill. Hazardous reaction: measure explosive gas-air mixture. Reaction: dilute combustible gas/vapour with water curtain. Heat exposure: dilute toxic gas/vapour with water spray. Take account of toxic/corrosive precipitation water.	
Methods for cleaning up	: Take up liquid spill into absorbent material, e.g.: dry sand/earth or powdered limestone. Scoop absorbed substance into closing containers. See "Material-handling" for suitable container materials. Carefully collect the spill/leftovers. Small quantities of liquid spill: neutralize with acid solution. Wash away neutralized product with plentiful water. Damaged/cooled tanks must be emptied. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.	

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage	9
7.1. Precautions for safe handling	
Additional hazards when processed	: May be corrosive to metals.
Precautions for safe handling	: Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Handle and open the container with care. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Keep away from naked flames/heat. Observe very strict hygiene - avoid contact. Keep container tightly closed. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe dust, mist or spray. Avoid contact during pregnancy/while nursing.
Hygiene measures	: Wash Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work thoroughly after handling. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.
7.2. Conditions for safe storage, inc	uding any incompatibilities
Technical measures	: Comply with applicable regulations.
10/16/2020	EN (English LIS) 2/0

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : direct sunlight, heat sources, Keep container closed when not in use. Keep container closed when not in use.	
Incompatible products	: Strong bases. Strong acids.	
Incompatible materials	: Sources of ignition. Direct sunlight.	
Maximum storage period	: 1 year	
Storage temperature	: > 15 °C	
Heat-ignition	: KEEP SUBSTANCE AWAY FROM: heat sources.	
Information on mixed storage	: KEEP SUBSTANCE AWAY FROM: combustible materials. (strong) acids. metals.	
Storage area	Store in a cool area. Keep out of direct sunlight. Store in a dry area. Store in a dark area. Keep locked up. Provide for a tub to collect spills. Keep only in the original container. Meet the legal requirements.	
Special rules on packaging	: SPECIAL REQUIREMENTS: hermetical. dry. clean. correctly labelled. meet the legal requirements. Secure fragile packagings in solid containers.	
Packaging materials	: SUITABLE MATERIAL: stainless steel. nickel. polyethylene. polypropylene. glass. stoneware/porcelain. MATERIAL TO AVOID: lead. aluminium. copper. tin. zinc. bronze.	

SECTION 8: Exposure controls/personal protection

8.1.	Control parameters	
Clean	Тар	
USA - ACGIH - Occupational Exposure Limits		
ACGI	H Ceiling (mg/m³)	2 mg/m³
potassium hydroxide, 45%= <conc<50%, (1310-58-3)<="" aqueous="" solutions="" th=""></conc<50%,>		
No additional information available		

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Materials for protective clothing:

GIVE EXCELLENT RESISTANCE: nitrile rubber. GIVE GOOD RESISTANCE: No data available. GIVE LESS RESISTANCE: chlorinated polyethylene. styrene-butadiene rubber. nitrile rubber/PVC. GIVE POOR RESISTANCE: PVA. natural fibres

Hand protection:

Gloves. Wear protective gloves

Eye protection:

Chemical goggles or face shield. Face shield

Skin and body protection:

Corrosion-proof clothing. Wear suitable protective clothing

Respiratory protection:

Wear gas mask with filter type B if conc. in air > exposure limit. Wear appropriate mask

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties		
9.1. Information on basic physical and chemical properties		
Physical state	: Liquid	
Appearance	: Clear liquid.	
Color	: Colorless	
Odor	: slight Characteristic odour	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Odor threshold	: No data available
рН	: > 13
pH solution	: > 12
Melting point	: No data available
Freezing point	: 12 °C
Boiling point	: >100 °C
Critical temperature	: Not Applicable
Critical pressure	: Not Applicable
Flash point	: Not Applicable
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not Applicable Non flammable.
Vapor pressure	: < 1.2 hPa
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 1.07 g/cm ³
Solubility	: Soluble in water. Water: 100 %
Log Pow	: <-3.9
Auto-ignition temperature	: Not Applicable
Decomposition temperature	: No data available
Viscosity, kinematic	: < 350 mm²/s
Viscosity, dynamic	: < 0.05 Pa.s
Explosion limits	: Not Applicable Not Applicable
Explosive properties	: Not applicable.
Oxidizing properties	: None.
9.2. Other information	
VOC content	: 0%

SECTION 10: Stability	y and reactivity

10.1. Reactivity

On heating: release of corrosive gases/vapours. Absorbs the atmospheric CO2. Violent exothermic reaction with (some) acids. Reacts with (some) metals: release of highly flammable gases/vapours (hydrogen). Thermal decomposition generates : Corrosive vapors.

10.2. Chemical stability

Stable under normal conditions. Absorbs the atmospheric CO2. Hygroscopic. Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. Thermal decomposition generates : Corrosive vapors.

SECTION 11: Toxicological information	
11.1. Information on toxicological effects	
Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
ATE US (oral)	341.25 mg/kg body weight

Clean Tap Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

potassium hydroxide, 45%= <conc<50%, aqu<="" th=""><th>ueous solutions (1310-58-3)</th></conc<50%,>	ueous solutions (1310-58-3)
LD50 oral rat	273 mg/kg (Rat)
ATE US (oral)	273 mg/kg body weight
Skin corrosion/irritation	: Causes severe skin burns and eye damage.
	pH: > 13
Serious eye damage/irritation	: Eye damage, category 1, implicit
	pH: > 13
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: < 350 mm²/s
Likely routes of exposure	: Dermal. Ingestion. Inhalation. oral. Skin and eye contact.
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries	: Causes severe skin burns and eye damage.
Symptoms/injuries after inhalation	: EXPOSURE TO HIGH CONCENTRATIONS: Dry/sore throat. Coughing. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. FOLLOWING SYMPTOMS MAY APPEAR LATER: Possible laryngeal spasm/oedema. Risk of lung oedema. Respiratory difficulties.
Symptoms/injuries after skin contact	: Caustic burns/corrosion of the skin. Slow-healing wounds.
Symptoms/injuries after eye contact	: Corrosion of the eye tissue. Permanent eye damage.
Symptoms/injuries after ingestion	 Vomiting. Diarrhoea. Burns to the gastric/intestinal mucosa. Possible esophageal perforation. Bleeding of the gastrointestinal tract. Shock. AFTER ABSORPTION OF HIGH QUANTITIES: Disturbances of consciousness.
Chronic symptoms	: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Dry skin. Skin rash/inflammation. Possible inflammation of the respiratory tract.

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	: Classification concerning the environment: not applicable.
Ecology - water	Mild water pollutant (surface water). Ground water pollutant. Maximum concentration in drinking water: 200mg/l (sodium) (Directive98/83EC). Harmful to fishes. Harmful to invertebrates (Daphnia). pH shift

potassium hydroxide, 45%= <conc<50%, (1310-58-3)<="" aqueous="" solutions="" th=""></conc<50%,>	
LC50 fish 2	80 mg/l (LC50; 96 h)
12.2. Persistence and degradability	
Clean Tap	
Persistence and degradability	Not established.
potassium hydroxide, 45%= <conc<50%, aque<="" td=""><td>ous solutions (1310-58-3)</td></conc<50%,>	ous solutions (1310-58-3)
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the components available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
12.3. Bioaccumulative potential	
Clean Tap	
Log Pow	< -3.9
10/16/2020	EN (English US) 6/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ccording to Federal Register / Vol. 77, No. 58 / Monday, I	Varch 26, 2012 / Rules and Regulations
Clean Tap	
Bioaccumulative potential	Not established.
potassium hydroxide, 45%= <conc<50%, aqu<="" th=""><th>eous solutions (1310-58-3)</th></conc<50%,>	eous solutions (1310-58-3)
Bioaccumulative potential	Not bioaccumulative.
12.4. Mobility in soil	
No additional information available	
12.5. Other adverse effects	
Other adverse effects	: May cause pH changes in aqueous ecological systems.
Other information	: Avoid release to the environment.
SECTION 13: Disposal consideration	S
13.1. Disposal methods	
Product/Packaging disposal recommendations	: Remove waste in accordance with local, state and/or national regulations. Remove for physico- chemical/biological treatment. Do not discharge into surface water. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to
Additional information	: Clean up even minor leaks or spills if possible without unecessary risk.
Ecology - waste materials	: Avoid release to the environment.
SECTION 14: Transport information	
Department of Transportation (DOT) n accordance with DOT	
Transport document description	: UN1814 Potassium hydroxide, solution, 8, II
JN-No.(DOT)	: UN1814
Proper Shipping Name (DOT)	: Potassium hydroxide, solution
Class (DOT)	: 8 - Class 8 - Corrosive material 49 CFR 173.136
Packing group (DOT)	: II - Medium Danger
Hazard labels (DOT)	: 8 - Corrosive
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
OOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Special Provisions (49 CFR 172.102)	 B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T7 - 4 178.274(d)(2) Normal
DOT Packaging Exceptions (49 CFR 173.xxx)	(59 F) and 50 C (122 F), respectively. : 154
DOT Quantity Limitations Passenger aircraft/rail 49 CFR 173.27)	
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 30 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

10/16/2020

EN (English US)

passenger vessel.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Other	: 52 - Stow "separated from" acids
Emergency Response Guide (ERG) Number	: 154
Other information	: No supplementary information available.
Transportation of Dangerous Goods	

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

SECTION 15: Regulatory information		
15.1. US Federal regulations		
Clean Tap		
Listed on the United States TSCA (Toxic Substances Control Ac Not subject to reporting requirements of the United States SARA		
All components of this product are listed, or excluded from listing Substances Control Act (TSCA) inventory except for:	, on the United States Environmental	I Protection Agency Toxic
potassium hydroxide, 45%= <conc<50%, aqueous="" solutions<="" td=""><td>CAS-No. 1310-58-3</td><td>5 - 15%</td></conc<50%,>	CAS-No. 1310-58-3	5 - 15%

15.2. International regulations

CANADA

EU-Regulations

National regulations

No additional information available

15.3. US State regulations

Clean Tap	
State or local regulations	U.S Massachusetts - Right To Know List U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
potassium hydroxide, 45%= <conc<50%, aqueous="" solutions(1310-58-3)<="" td=""><td>U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List</td></conc<50%,>	U.S Massachusetts - Right To Know List; U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : None.

Full text of H-phrases:

H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard	: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.	
NFPA fire hazard	: 0 - Materials that will not burn.	
NFPA reactivity	 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently. 	
Hazard Rating		
Health	: 2 Moderate Hazard - Temporary or minor injury may occur	
Flammability	: 0 Minimal Hazard - Materials that will not burn	
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.	
Personal Protection	: D	
	D - Face shield and eye protection, Gloves, Synthetic apron	

SDS US (GHS HazCom 2012)

Terms and Conditions. This Safety Data Sheet (SDS) is designed only as guidance for the product to which it applies. To the greatest extent permitted by applicable law, nothing contained herein creates any legal obligation including contractual obligations, expressed or implied warranties, including any warranties of merchantibility or fitness for a particular purpose; or confers any intellectual property rights, including rights to use trademarks or a license to use patents, issued or pending. The information contained herein is based on the manufacturer's own study and the work of others, and is subject to change at any time without further notice. There is no warranty, expressed or implied, as to the accuracy, completeness or adequacy of the information contained herein, and neither the provider nor the manufacturer (nor the agents, directors, officers, contractors or employees of either) are liable to any party for any damages of any nature, including direct, special, or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishings of any information in this SDS, or in any other way related (directly or indirectly) to this SDS. The receipt and use of this information constitutes consent to these terms and conditions.