

Product Information



FOAM-BRITE SELF-FOAMING ACID DETERGENT

CLEANS

- Tank exteriors
- Floors
- Conveyors
- Parts and utensils
- Other environmental surfaces

FEATURES/BENEFITS

- Self-Foaming – generates copious, stable foam
 - No foam additives needed
 - Increased dwell time to penetrate, dislodge and suspend difficult soils
 - Ideal for use in air operated and hand held foam units
- Economical – concentrated acid
- High detergency – makes an excellent manual cleaner
- Concentrated blend of surfactants – effectively penetrates mineral scales
- Free rinsing – leaves no residue
- Effective in hard water conditions

DESCRIPTION

- FOAM-BRITE is a concentrated liquid, self-foaming acid cleaner, formulated to provide copious foam when used in air-injected foam generators, and for uses as a high foaming manual acid cleaner. FOAM-BRITE effectively removes beerstone, hard water scale, and other mineral deposits from surfaces, returning stainless steel to its original shine. FOAM-BRITE is concentrated, providing enhanced cleaning economies and high performance.

USE DIRECTIONS

- Foam cleaning: Add FOAM-BRITE to the foam solution tank at a ratio of 4 to 6 ounces per gallon of hot water. (dilutions will vary dependent on soil type and load). Apply cleaning solutions to surfaces being cleaned. Allow a dwell time of 10-20 minutes on stainless steel surfaces - however, do not allow solution to dry. Rinse well with fresh water.

The information contained herein is to our knowledge, true and accurate. Because conditions of use are beyond our control, we make no warranty or representation, expressed or implied, except that the products discussed herein conform to the chemical descriptions shown on their labels. Nothing contained herein should be construed as permission or recommendation to infringe any patent. No agent, representative, or employee of this company is authorized to vary any items of the notice.

Ace Chemical Products, Inc. • Milwaukee, Wisconsin 53224 • 1-800-248-8515 • brewcitysolutions.com

Product Information



FOAM-BRITE

USE DIRECTIONS (continued)

- When foam acid cleaning of ferrous metals, a dwell time of 5-10 minutes should be employed. This should be followed by a rinse with an appropriate alkaline cleaner to provide neutralization. A final rinse should then be performed with clear water.
- For specific use recommendations, or answers to any cleaning or sanitation questions you may have, contact us at 1-800-248-8515.

TECHNICAL DATA

FORM	Liquid
COLOR	Brown
ODOR	Slight acidic
POUNDS PER GALLON	10.1
pH of a 1% SOLUTION	2.2
FOAMING	High
BIODEGRADABLE	Complete
COMPATIBILITY	Avoid soft metals

6055-L03-js

Always observe label precautionary statements and follow the information provided in our Material Safety Data Sheet for this product. A safety video presentation is available on request.

The information contained herein is to our knowledge, true and accurate. Because conditions of use are beyond our control, we make no warranty or representation, expressed or implied, except that the products discussed herein conform to the chemical descriptions shown on their labels. Nothing contained herein should be construed as permission or recommendation to infringe any patent. No agent, representative, or employee of this company is authorized to vary any items of the notice.

Ace Chemical Products, Inc. • Milwaukee, Wisconsin 53224 • 1-800-248-8515 • brewcitysolutions.com